

ALKALI - RESISTANT

EN

Coated, alkali-resistant, fiberglass mesh 160g/m²
Roll size: 1m x 50m
For general reinforcement and industrial applications.

PL

Powlekania, odporna na alkalia, siatka 160g/m²
Wymiary rolki: 1m x 50m
Do ogólnego zbrojenia i zastosowań przemysłowych.

DE

Beschichtetes, alkalibeständiges Drahtgewebe 160 g/m²
Rollenmaße: 1 m x 50 m
Für allgemeine Bewehrungs- und Industrieranwendungen.

CZ

Potahovaná, odolná vůči alkáliím, gramáž ok 160 g/m²
Rozměry role: 1 m x 50 m
Pro všeobecné vyztužení a průmyslové aplikace.

Storage

Packed rolls are to be stored in dry rooms. Storing temperature is: from -10°C to + 50°C.

The rolls are packed vertically in cardboard, on a plywood pallet.

REN

RenderEuroNet

160 g/m²

Fiberglass mesh
Glasfasernetz
Siatka z włókna szklanego
Sklolaminátová síťovina

Items		Datas	
Weave type		Interlace	
Weight after coating (g/m ²)		162,1	
Coating content (%)		15,9	
Roll width (mm)		1000	
Roll length (m)		50,2	
Thickness		0,5	
Density	wrap	5,1	
	weft	5,2	
Tensile strength (N/5cm)	After manufacturing	warp	1611
		weft	1892
	After alkalia	warp	1188
		weft	1315