

DECLARATION OF PERFORMANCE No. DOP-01/2026

1. Unique identification code of the product type:

Fiberglass mesh 160g/m² - alkali resistant, RAL 5015, Render EuroNet, 1m x 50m, 8kg/roll

2. Intended use:

Reinforcement of base coat in external thermal insulation composite systems (ETIC)

3. Manufacturer/Importer to EU:

Dipodeno s.r.o
Teslova 1129/2b, Privoz
70200 Ostrava
Ceska Republika
CZ 23381787
ICO 23381787

4. Authorized representative:

Not applicable

5. System of assessment and verification of constancy of performance (AVCP):

System 3

6. European assessment document:

Based on ETAG-004 guideline for external thermal insulation composite systems (ETICS)

7. Declared performance:

Essential characteristics
Performance Mass per unit area 162.1 g/m²
Mesh type: Interlace
Tensile strength (warp, initial) 1611 N/5 cm
Tensile strength (weft, initial) 1892 N/5 cm
Tensile strength after alkali exposure (warp) 1188 N/5 cm
Tensile strength after alkali exposure (weft) 1315 N/5 cm
Alkali resistance
Retained strength $\geq 70\%$ Width 1000 mm
Length 50.2 m.
Thickness 0.5 mm

8. The performance of the product identified above is in conformity with the declared performance.

This declaration of performance is issued under the sole responsibility of the importer/manufacturer identified above.

Signed for and on behalf the importer/manufacturer:

Dipodeno s.r.o
Teslova 1129/2b, Privoz
70200 Ostrava
Ceska Republika
CZ23381787

Łukasz Chmielewski

President of the
Management Board

