



## **DECLARATION OF PERFORMANCE**

### **No. DOP-01/2026**

#### **1. Unique identification code of the product type:**

Fiberglass mesh 160g/m<sup>2</sup> - alkali resistant, RAL 5015, Render EuroNet, 1m x 50m, 8kg/roll

#### **2. Intended use:**

Reinforcement of base coat in external thermal insulation composite systems (ETIC)

#### **3. Manufacturer/Importer to EU:**

Dipodeno s.r.o  
Teslova 1129/2b, Privoz  
70200 Ostrava  
Ceska Republika  
CZ 23381787  
ICO 23381787

#### **4. Authorized representative:**

Not applicable

#### **5. System of assessment and verification of constancy of performance (AVCP):**

System 3

#### **6. European assessment document:**

Based on ETAG-004 guideline for external thermal insulation composite systems (ETICS) - EAD 040016-00-0404

#### **7. Declared performance:**

Essential characteristics  
PerformanceMass per unit area 162.1 g/m<sup>2</sup>  
Mesh type: Interlace  
Tensile strength (warp, initial) 1611 N/5 cm  
Tensile strength (weft, initial) 1892 N/5 cm  
Tensile strength after alkali exposure (warp) 1188 N/5 cm  
Tensile strength after alkali exposure (weft) 1315 N/5 cm  
Alkali resistance  
Retained strength  $\geq$  70%Width1000 mm  
Length 50.2 m.  
Thickness 0.5 mm

#### **8. The performance of the product identified above is in conformity with the declared performance.**

This declaration of performance is issued under the sole responsibility of the importer/manufacturer identified above.

Signed for and on behalf the importer/manufacturer: